

PRODUCT DATA SHEET

Sika® Wall Décor

READY TO USE WATER RESISTANT WHITE CEMENT BASED PUTTY FOR INDOOR AND OUTDOOR FINISHING APPLICATIONS.

DESCRIPTION

Sika® Wall Décor is ready to use water resistant white cement based finishing / smoothing material for indoor and outdoor plastered surfaces.

USES

- White cement based finishing / smoothing material for indoor and outdoor plastered surfaces
- Renders a smooth and durable surface and acts as an under layer for all kinds of decorative paints.

CHARACTERISTICS / ADVANTAGES

- Excellent white look & smooth finish
- Excellent water resistant capability
- Reduces paint consumption
- Never peels off
- No flaking
- No Blistering
- No Chalking
- Good breathability
- Superb Bonding- White Cement base provides great adhesion to walls
- Better Coverage
- Can be applied on moist surface
- Excellent workability & ease of application
- Can be stained with a good quality water based Stain for light shades
- Pre-tinted form can be used as a decorative coating without the use of conventional paint

PRODUCT INFORMATION

Packaging	30 kg & 40 kg bag		
Appearance / Colour	White lump free powder		
Shelf Life	8 months from date of production.		
Storage Conditions	8 months from date of production if stored properly in unopened original packaging. Protect from frost.		
Density	0.85-1.05kg/l (Bulk Density)		
Consumption	~ 1.0 kg powder / m ² / mm thickness. Sika® Wall Décor covers an approx 18-22 sft / kg /mm in 2 coats on smooth finish substrate in optimum conditions.		
Pot Life	~90 min		
Drying Time	Initial setting time	≥ 100 minutes	According to EN 196
	Final setting time	≤ 500 minutes	

SUBSTRATE QUALITY / PRE-TREATMENT

The substrate should be free from grease, oil and loosely adhering particles.

Clean the surface with the help of emery stone, putty blade or wire brush. Moisten the wall with sufficient quantity of clean water. There should not be any mildew or algae on the surface.

APPLICATION

First mix the supplied Sika® Wall Décor with 38 to 42% clean water & Continue mixing until a homogeneous lump free paste of desired consistency is obtained. Apply 1st coat of Sika® Wall Décor uniformly on already moistened surface with the help of putty blade or trowel. Mix only that quantity which can be applied within workable time. After surface drying & hardening of the 1st coat it should be prepared with fine waterproof emery paper before apply 2nd coat with fresh material. The total thickness of 2 coats should be maximum 1.5 mm. Uneven thickness due to unskilled application may cause problem. Finishing should be done by skilled POP applicators.

CLEANING OF TOOLS

Clean all tools and application equipment with petrol immediately after use.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika India Pvt. Ltd.

620, Diamond Harbour Road
Commercial Complex II
Kolkata - 700 034
Tel : +91 33 24472448
Fax : +91 33 23978688
Mail : info.india@in.sika.com



Product Data Sheet
Sika® Wall Décor
September 2019, Version 01.02
020406010030000044

SikaWallDcor-en-IN-(09-2019)-1-2.pdf